

Score changes dice to rounding

FIGURE 1 IRS COVER SHEET

3010304

100006 TOL

100005

1010304

00000

08MT004

			Groun	d Wa	ter 3	oute Work Sh	••:			
	Rating Factor		٨	ssigr (Circ		ziue ne)	Muiti-	Long	Max. Score	Ref. (Section)
1	Observed Release	L.	0			45	1	45	45	3.1
	If observed releas	982					_			
2	Route Characteris Depth to Aquifer Concern		0	1 :	2 3		2		6	3.2
	Net Precipitation Permeability of t Unsaturated Zo	ne	0	850 04	2 3		1	3 1	3	
	Physical State		0	1	2 3		1		3	
		T	otal Rou	té Cl	narac	teristics Score	Š		15	c
<u>.</u>	Containment		0	1	2 3		1		3	3.3
4	Waste Characteris Toxicity/Persisti Hazardous Wast Quantity	ence	0	3 (5 9	12 15 (18) 4 5 6 7 (3 1	8	18	3.4
		Т	otal Was	te C	arac	teristics Score)	26	25	
3	Targets Ground Water U. Cistance to Near Well/Population Served	rest	0 12 24	1 4 16 30	2 (5 18 (32	3 20 10 15 40	3	9 20	9	3.5
								*		
			Tot	al Ta	rget	Score		29	49	N I
<u>5</u>	_	multiply []			5 x	3	33	930	57.330	
7	Divide line 6 5	y 57.330 an	a multip	y Dy	100		Sgw=	59.	18	

FIGURE 2
GROUND WATER ROUTE WORK SHEET

08 MTCC4 Surface Water Route Work Sheet Assigned Value Multi-Max. Set. Rating Factor Score Circle Cner olier Score (Section) **1** 45) Observed Release 45 4.1 If observed release is given a value of 45, proceed to line 41. If observed release is given a value of 0, proceed to line [2]. 2 Route Characteristics 4.2 Facility Slope and Intervening 0 1 2 3 3 Terrain 1-yr. 24-hr. Rainfall Distance to Nearest Surface 1 2 3 Water **Physical State** 0 1 2 3 **Total Route Characteristics Score** 15 3 Containment 0 1 2 3 1 3 Waste Characteristics 4.4 18 Toxicity / Persistence 0 1 2 3 4 5 6 7 3 Hazardous Waste Quantity **Total Waste Characteristics Score** 26 25 3 Targets 4.5 Surface Water Use Distance to a Sensitive Environment Population Served/Distance 16 to Water Intake Downstream Total Targets Score 55 if line 1 is 45, multiply 1 x 4 x 5 is 0. multiply 2 x 3 x 4 x 5 If line [1] 54.350 Divide line 6 by 64,350 and multiply by 100 Ssw -

FIGURE 7
SURFACE WATER ROUTE WORK SHEET

08MTC04

			Air	Rou	ite '	Nork	Shee	et				
	Rating Factor			igne Circle		aiue			Muiti		Max. Score	Ref. (Section)
1	Observed Release		(0)			45			1	10	45	5.1
	Date and Location:											
	Sampling Protocol:								71.	•		
	If line 1 is 0, the			_		•			•	- 4		
2	Waste Characteristic	cs	0	. 2	3				1		3	5.2
	Incompatibility				2				9			*:
	Toxicity Hazardous Waste Quantity	*	0	2	3	4 5	5	7 8	3		8	
*	Commy											
						*					•	
	*											
		Total	al Waste	Cha	arac	teristi	cs S	core			20	
3	Tergets											5.3
STEEL S	Population Within			12		12			1		30	
	4-Mile Radius Distance to Sensiti		J 21 2	27					2		5	
	Environment		· ·	•	3				4		9	
	Land Use		0 1	2	3				1		3	
	*									•		
						74						
	(#)	*								*		
	Γ		Tota	Tar	Çet	Scc			•		39	
4	Multiply 1 x 2	x 3									35.100	
3	Civide line 4 by	35.100 and	multiply	by '	100				· s .	0		

FIGURE 9
AIR ROUTE WORK SHEET

		GENTOU4
:-	s	s ²
Groundwater Route Score (Sgw)	59.18	3502.27
Surface Water Route Score (S _{SW})	47.27	2234.45
Air Route Score (Sa)	10	0
$S_{gw}^2 + S_{sw}^2 + S_{1}^2$		5736.72
$\sqrt{s_{gw}^2 + s_{sw}^2 + s_a^2}$		75.74
$\sqrt{s_{gw}^2 + s_{sw}^2 + s_a^2} / 1.73 = s_M =$		43.78

FIGURE 10 WORKSHEET FOR COMPUTING $S_{\overline{M}}$

Fire and Explosion Work Sheet Max. Assigned Value :Julti-Pet. Rating Factor Score ::ier (Circle One) Score i Sections I Containment 3 3 7.1 1 Waste Characteristics 7.2 Direct Evidence Ignitability C 3 2 3 Reactivity 2 Incompatibility Hazardous Waste Quantity Total Waste Characteristics Score 20 3 Targets 7.3 Distance to Nearest 0 1 2 3 4 5 5 Population Distance to Nearest 0 1 2 3 3 Building Distance to Sensitive 0 1 2 3 Environment Land Use Population Within 0 1 2 3 4 5 2-Mile Radius **Buildings** Within 0 1 2 3 4 5 5 2-Mile Radius Total Targets Score 24 Multiply 1 x 2 x 3 1.440 5 Divide line 4 by 1.440 and multiply by 100 SFE -

FIGURE 11
FIRE AND EXPLOSION WORK SHEET

ENTERED AND 1 1983

				OUM	104
		Direct Contact Work S	iheet		
	Rating Factor	Assigned Value (Circle One)	Multi-	Score Max.	Ref.
1	Cbserved Incident	(3) 45	1	- 45	3.1
•	If line 1 is 45, proceed to	Section 1997 Section 1997		1940 T	
2	Accessibility	0 1 2 3	1	3	8.2
3	Containment	0 15	1	15	8.3
4	Waste Characteristics Toxicity	0 1 2 3	5	15	9.4
3	Targets Population Within a 1-Mile Radius	0 1 2 3 4 5	4	20	3.5
	Distance to a Critical Habitat	0 1 2 3		12	
	No-	T. SCORED	٠		
2				×	
		Total Targets Score		32	
	line 1 is 45, multiply [line 1 is 0, multiply 2			21,500	
D 5	livide line 6 by 21,600 ar	nd multiply by 100	Spc -	0	

FIGURE 12 DIRECT CONTACT WORK SHEET

MILLTOWN GROUNDWATER CONTAMINATION

In May of 1981, routine samples were taken from drinking water wells located in the community of Milltown, Montana, by Missoula County Environmental Health Officials. Of the seven wells tested, four of these wells showed elevated levels of arsenic, based on State Department of Health and Environmental Sciences laboratory analyses, that exceeded the EPA Interim Primary Drinking Water Standard for arsenic. Subsequent analyses by DHES confirmed in December of 1981 that the four wells, serving a total of 33 residences, were contaminated with up to ten (10) times the Drinking Water Standard of 0.05 mg/l As. Residents were advised to not utilize this water for drinking and cooking and to seek alternate supplies of potable water.

Tests on other wells in the area indicate zero or minimally-detectable levels of arsenic, but these wells are apparently not currently capable of supplying affected Milltown consumers. Analyses performed in 1979 detected virtually no arsenic in residents' well water. Montana DHES officials have determined that the arsenic contaminants are 50 percent trivalent and 50 percent pentavalent; at this time no further contaminant characterization is available.

Speculation on the sources of contamination is divided between leachate from an old, abandoned landfill located east of town (contents unknown) or dissolution of metals from mill tailings (sediments) historically deposited behind Milltown Dam located south and immediately adjacent to the town and across the Clark Fork River. Initial analyses of deposited sediment elution indicate low levels (0.09 mg/l) total recoverable arsenic. No samples of the landfill cores have yet been taken.

Milltown is located on an alluvial isthmus between the Clark Fork River and the Blackfoot River. Groundwater hydrology is principally influenced by these two surface streams, and the principle subsurface strata is cobble and boulders. A study of the hydrogeology of the Milltown area was undertaken by the University of Montana in Missoula, largely supported by EPA contract dollars. Results of the study are not available yet, but preliminary indications are that no one source can be identified as the instigator of the above arsenic contamination.

Based on evaluation by the Montana Department of Health and Environmental Sciences and the Environmental Protection Agency Montana Office, of the information to date, it was decided that further investigation or remedial action could best be addressed by including the site on the National Contingency Plan list of priority hazardous waste sites currently being completed by EPA.



DOCUMENTATION RECORDS FOR HAZARD RANKING SYSTEM

INSTRUCTIONS: The purpose of these records is to provide a convenient way to prepare an auditable record of the data and documentation used to apply the Hazard Ranking System to a given facility. As briefly as possible summarize the information you used to assign the score for each factor (e.g., "Waste quantity = 4,230 drums plus 800 cubic yards of sludges"). The source of information should be provided for each entry and should be a bibliographic-type reference that will make the document used for a given data point easier to find. Include the location of the document and consider appending a copy of the relevant page(s) for ease in review.

FACILITY NAME: _	MILLTOWN	RESERVOI	R SEDIMENTS
LOCATION:	MILLTOWN		CLARK FORK FIVER

GROUND WATER ROUTE

1 OBSERVED RELEASE

Contaminants detected (5 maximum):

ARSENIC HAS BEEN DETECTED UP TO 10 X DWS.

ALSO FOUND CU, ZN, Pb, MN.

Rationale for attributing the contaminants to the facility:

SEE ATTACHED DRAFT LETTER

10/3/82 JOHNNE MOORE

UNIV. DE MONTANA

2 ROUTE CHARACTERISTICS

Depth to Aquifer of Concern

Name/description of aquifers(s) of concern:

Depth(s) from the ground surface to the highest seasonal level of the saturated zone [water table(s)] of the aquifer of concern:

Depth from the ground surface to the lowest point of waste disposal/ storage:

Net 1	Precipi	tat	ion					
Mean	annual	or	seasonal	precipitation	(list	months	for	seasonal):

Mean annual lake or seasonal evaporation (list months for seasonal):

Net precipitation (subtract the above figures):

Permeability of Unsaturated Zone

Soil type in unsaturated zone:

Permeability associated with soil type:

Physical State

Physical state of substances at time of disposal (or at present time for generated gases):

* * *

CONTAINMENT

Containment

Method(s) of waste or leachate containment evaluated:

Method with highest score:

4 WASTE CHARACTERISTICS

Toxicity and Persistence

Compound(s) evaluated:

ARSENIC COMPOUNDS

LEAD

ZINC

COPPER

Compound with highest score:

ARSENIC

3 - PERSISTENCE (METALS)

3-TOXICITY (SAX, 44 ed.)

SCORE = 18

Hazardous Waste Quantity

Total quantity of hazardous substances at the facility, excluding those with a containment score of 0 (Give a reasonable estimate even if quantity is above maximum):

SEDIMENT: 511,680 TONS - IXIDG TONS

SCORE = 8

Basis of estimating and/or computing waste quantity:

PERSONAL COMMUNICATION N/

ELAINE BIZO, MISSOULA COUNTY

DR. WM. WOESSNER, UNIV. OF MONTANA

5 TARGETS

Ground Water Use

Use(s) of aquifer(s) of concern within a 3-mile radius of the facility:

DRINKING WATER - NO OTHER SOURCE AVAILABLE

INJUSTRIAL

I RRIGATION

SCORE = 3

Distance to Nearest Well

Location of nearest well drawing from aquifer of concern or occupied building not served by a public water supply:

WELL NO. 9A (WOESSNER), EAST OF 207 BRDST., MILLIDUM
MISSOUR CO.: NWK SEK NEK NEK SWA SEC. 21, RANGE 13N, TOWNSHED 18W
COMMUNITY WELL FOR SEVERAL MILLITOWN RESIDENTS.

Distance to above well or building:

APPROX. 425 St. NORTH FROM RESERVOIR.

SCORE = 4 ON MATRIX

Population Served by Ground Water Wells Within a 3-Mile Radius

Identified water-supply well(s) drawing from aquifer(s) of concern within a 3-mile radius and populations served by each:

35 HOMES IN MILLTOWN SERVED BY CONTANINATED WELLS.

Computation of land area irrigated by supply well(s) drawing from aquifer(s) of concern within a 3-mile radius, and conversion to population (1.5 people per acre):

INFORMATION NOT PRESTENTLY AVAILABLE

Total population served by ground water within a 3-mile radius:

35 HOMES X 3.8 INDIVIDUALS/HOME = 133

SCORE = 2 ON MATES!

DIST POP. MATRIX SCORE = 20

SURFACE WATER ROUTE

1 OBSERVED RELEASE

Contaminants detected in surface water at the facility or downhill from it (5 maximum):

Rationale for attributing the contaminants to the facility:

SEE J. MOORE DRAFT LETTER 10/3/82.

ALSO BARREY THESES
ARE IN RESERVOIR (RIVER) BOTTOM SEDIMENTS

2 ROUTE CHARACTERISTICS

Facility Slope and Intervening Terrain

Average slope of facility in percent:

Name/description of nearest downslope surface water:

Average slope of terrain between facility and above-cited surface water body in percent:

Is the facility located either totally or partially in surface water?

Is the facility completely surrounded by areas of higher elevation?
1-Year 24-Hour Rainfall in Inches
3
Distance to Nearest Downslope Surface Water
Physical State of Waste
* * *
€
3 CONTAINMENT
Containment
Method(s) of waste or leachate containment evaluated:
:

Method with highest score:

4 WASTE CHARACTERISTICS

Toxicity and Persistence

Compound(s) evaluated

SEE GROWDWATER RATIONALE PREVIOUS PAGE 4

Compound with highest score:

ARSENIC

Hazardous Waste Quantity

Total quantity of hazardous substances at the facility, excluding those with a containment score of 0 (Give a reasonable estimate even if quantity is above maximum):

SEE GROUNDWATER RATIONALE PREVIOUS PAGE 4.

Basis of estimating and/or computing waste quantity:

5 TARGETS

Surface Water Use

Use(s) of surface water within 3 miles downstream of the hazardous substance:

I RECREATION

SCORE = Z

HAZARDOUS SUBSTANCE HAS BEEN PERIODECALLY FLUSHED FROM RESERVOIR INTO RIVER. Is there tidal influence?

No.

Distance to a Sensitive Environment

NIA

Distance to 5-acre (minimum) coastal wetland, if 2 miles or less:

Distance to 5-acre (minimum) fresh-water wetland, if I mile or less:

Distance to critical habitat of an endangered species or national wildlife refuge, if I mile or less:

SCOPE = 0

Population Served by Surface Water

Location(s) of water-supply intake(s) within 3 miles (free-flowing bodies) or 1 mile (static water bodies) downstream of the hazardous substance and population served by each intake:

MONTANA DNRC DATA AVAILABLE

ON SURFACE WATER WITHDRAWAYS

ALL WITHDRAWAYS FOR IRRIGATION

DIVERSION COORDINATES AVAILABLE @ EPA-MO.

ALSO SCS DATA (PERSONAL COMMUNICATION; BEN HARI
ALL IRRIGATION & 2000 St. FROM RIVER.

Computation of land area irrigated by above-cited intake(s) and conversion to population (1.5 people per acre):

DNRC DATA: 592 ACRES

TOTAL

SCS DATA: PRINE & BANDY RANCH

DN BANDMANN FLATS: 96.5 ACRES

DN BANDMANN FLATS: 96.5 ACRES

Total population served:

SCORE = 20 MATRIX HRS P. 36

Name/description of nearest of above water bodies:

CLARK FORK RIVER (COLUMBIA RIVER SYSTEM) DOWNSTREAM OF MILLTOWN DAM.

Distance to above-cited intakes, measured in stream miles.

ALL DIVERSIONS & 3 STREAM MELES FROM DAM. COORDINATES AVAILABLE.

AIR ROUTE

1 OBSERVED RELEASE

Contaminants detected:

Date and location of detection of contaminants

Methods used to detect the contaminants:
Rationale for attributing the contaminants to the site:
* * *
2 WASTE CHARACTERISTICS
Reactivity and Incompatibility
Most reactive compound:
Most incompatible pair of compounds:

To	x	i	c	i	ty	
	_		_		_	

Most toxic compound:

Hazardous Waste Quantity

Total quantity of hazardous waste:

Basis of estimating and/or computing waste quantity:

* * *

3 TARGETS

Population Within 4-Mile Radius

Circle radius used, give population, and indicate how determined:

0 to 4 mi

0 to 1 mi

0 to 1/2 mi

0 to 1/4 mi

Distance to a Sensitive Environment

Distance to 5-acre (minimum) coastal wetland, if 2 miles or less:

Distance to 5-acre (minimum) fresh-water wetland, if 1 mile or less:

Distance to critical habitat of an endangered species, if I mile or Land Use Distance to commercial/industrial area, if I mile or less: Distance to national or state park, forest, or wildlife reserve, if 2 miles or less: Distance to residential area, if 2 miles or less: Distance to agricultural land in production within past 5 years, if 1 mile or less: Distance to prime agricultural land in production within past 5 years, if 2 miles or less:

Is a historic or landmark site (National Register or Historic Places and National Natural Landmarks) within the view of the site?